Specifikace



Eaton 275449

Eaton xEnergy Basic LV systems Low voltage switchgear. KL-29 terminal bar, 2 x 25 mm2 + 27 x 16 mm2, max. 63 A

Obecné specifikace	
PRODUCT NAME	Eaton xEnergy Basic installation component
CATALOG NUMBER	275449
EAN	4015082754495
PRODUCT LENGTH/DEPTH	18 mm
PRODUCT HEIGHT	8 mm
PRODUCT WIDTH	218 mm
PRODUCT WEIGHT	0.13 kg
COMPLIANCES	RoHS conform
MODEL CODE	KL-29

Additional information

FUNCTIONS	Additional equipment
SUITABLE FOR	Fine strand conductors Solid conductors Stranded conductors
USED WITH	Individual KL screw terminal Accessory consideration BF flat distribution board

Delivery program

ACCESSORY/SPARE PART TYPE	General
COLOR	Other
NOMINAL CURRENT	63 A
NUMBER OF POLES	Single-pole
TYPE	• Additional equipment • BF flat distribution board

Technical data - mechanical

CONDUCTOR CROSS SECTION, INPUT - MAX	25 mm²
CONDUCTOR CROSS SECTION, INPUT - MIN	1.5 mm²
CONDUCTOR CROSS SECTION, INPUT AWG - MAX	0 mm²
CONDUCTOR CROSS SECTION, INPUT AWG - MIN	0 mm²
CONDUCTOR CROSS SECTION, OUTPUT - MAX	16 mm²
CONDUCTOR CROSS SECTION, OUTPUT - MIN	1.5 mm²
CONDUCTOR CROSS SECTION, OUTPUT AWG - MAX	0 mm²
CONDUCTOR CROSS SECTION, OUTPUT AWG - MIN	0 mm²
HOUSING MATERIAL	Brass
MATERIAL	Metal
MOUNTING METHOD	Surface mounting Floor standing distribution board Flush mounting Screw
NUMBER OF INPUTS	2
NUMBER OF OUTPUTS	27
TERMINAL CAPACITY	25 mm² (2x) + 16 mm² (27x)
CONNECTION TYPE	Clamp Screwing

Zdroje

DECLARATIONS OF CONFORMITY	eaton-accessories-declaration-of-conformity-eu250233en.pdf
KATALOGY	eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf
POZNÁMKY K PRODEJI	eaton-f3a-flange-flyer-fl019005en-en-us.pdf

NÁZEV PROJEKTU:
ČÍSLO PROJEKTU:
PŘIPRAVIL:
DATUM:

Eaton Corporation Plc. Eaton House
30 Pembroke Road
Dublin 4, Irsko
Eaton.com

© 2026 Eaton. Všechna práva vyhrazena.

Sledujte nás na sociálních sítích, abyste získali nejnovější informace o produktech a podpoře.